

ZCUT SERIES

Tape Dispenser

Apply on different kinds of industry and tapes.

ZCUT-3EX/3EXRP

Specifications

ZCUT-3EX

Cutting Length	30-7000mm (When in manual use) 100-7000mm (When in auto use)
Tape Width	15-80mm
Max. Roll Diameter	240mm
Rated Voltage	AC 100-240V 50/60Hz 45W
Dimension	191(W) × 302(H) × 247(D)mm
Weight	9.5kg

ZCUT-3EXRP

Cutting Length	30-7000mm (When in manual use) 100-7000mm (When in auto use)
Tape Width	15-80mm
Max. Roll Diameter	150mm (Internal diameter 75mm)
Rated Voltage	AC 100-240V 50/60Hz 45W
Dimension	191(W) × 456(H) × 344(D)mm
Weight	10.5kg

ZCUT-3EX



ZCUT-3EXRP



RP Unit
For removing backing paper of double-sided tape

Features

- 01 The latest cutting method improves cutting styles.
- 02 Using L type blade of utility knife which is easy to get.
- 03 Tape feeding speed-up provides better work efficiency. Possible to cut max. 68 tapes/min. when craft tape is set with cutting length 100mm.

Adjust the width range in accordance with the selected tape (150mm · 250mm)

ZCUT-3150/3250

Specifications

ZCUT-3150

Cutting Length	40-9999mm
Tape Width	15-150mm
Max. Roll Diameter	200mm (Include Stand 400mm)
Rated Voltage	AC 100V/120V/220-240V 50/60Hz 600W
Dimension	332(W) × 298(H) × 247(D)mm
Weight	16kg

ZCUT-3250

Cutting Length	40-9999mm
Tape Width	15-250mm
Max. Roll Diameter	200mm (Include Stand 400mm)
Rated Voltage	AC 100V/120V/220-240V 50/60Hz 600W
Dimension	432(W) × 298(H) × 247(D)mm
Weight	18kg

ZCUT-3150

ZCUT-3250



ZCUT-3150 and ZCUT-3250 are using saw blade. Cutting edge is not 100% straight (little bit waving).

※ Power Voltage is maximum power dissipation when cutting (ZCUT-3150 and ZCUT-3250).
※ Please inform country of destination before purchasing.

Features

- 01 Durable for 24 hours operation.
- 02 Apply on Protection Film, Aluminum Foil and non-adhesive tapes.
- 03 Modify as depends on what kind of tape you use.