

## Illumino Meters



### ILLUMINOMETERS

	Order No.	Model No.	Dimensions (mm)	Weight (g)	JPY	Ref.No
1	1-5818-01	LM-331	65.5×35×190	210	¥ 19,100	053570
2	1-5818-02	LM-332			¥ 22,000	053570

#### ■ Feature

- It is with peak hold function displayed with peak value at the time of measuring.
- It is with fixed pin which can fix sensor to main part.

#### ■ Specification

- Sensor : Silicon Photo Diode



### DIGITAL ILLUMINOMETERS

	Order No.	Model No.	Dimensions (mm)	Weight (g)	JPY	Ref.No
3	6-6131-11	LX-1330D	71×37×148	approx. 275	¥ 27,500	053550
4	6-4047-11	LX-1332D			¥ 29,700	053550
5	6-6131-12	LX-204	55×38×170	approx. 190	¥ 22,000	053550

#### ■ Feature

- It is provided the data hold facility which fixes measured value.
- Measuring of place at distance by the separating sensor is possible (LX-1330D・LX-1332D).
- LX-204 : Integrated sensor type type which can be operated by single hand.

No.	1	2	3	4	5
Order No.	1-5818-01	1-5818-02	6-6131-11	6-4047-11	6-6131-12
Model No.	LM-331	LM-332	LX-1330D	LX-1332D	LX-204
Measuring Range (lx)	0.01~20000	0.1~200000	200/2000/20000	200/2000/20000/200000	
Resolution (lx)	0.01	0.1	200/0.1、2000/1、20000/10	200/0.1、2000/1、20000/10、200000/100	
Accuracy	± (5% rdg+10dgt)	± (5% rdg+10dgt)	± (5% rdg+4dgt/200・2000)、± (4% rdg+5dgt/20000)	± (5% rdg+4dgt/200・2000)、± (4% rdg+5dgt/20000・200000)	
Sampling (times/90°)	2.5	2.5	2.5	2.5	2.5
Max・Min Display	—	—	—	—	—
Hold	○	○	—	○	○
Memory	—	—	—	—	—
Backlight	○	○	—	—	—
Other Functions, Accessories	Peak Hold	Peak Hold	Stand・Carrying Case	Stand・Carrying Case	Soft Case
Power Supply	006P(9V) Battery×1 (included for testing)	006P(9V) Battery×1 (included for testing)	006P(9V) Battery×1 (sold separately)	006P(9V) Battery×1 (sold separately)	006P(9V) Battery×1 (sold separately)