

MCU Model / 1%RH

Door Opening / Closing: Once every 0.5 - 2hrs



MCU-201A
4.8 cf
(1-door type)



MCU-301A
11 cf
(2-door type)








MCU-401A
14 cf
(3-door type)



MCU-340A
11 cf
(2-door type)



MCU-580A
18.5 cf
(2-door type)



Features:

1. Can maintain an RH level of 1%.
2. Equipped with a digital RH Meter.
3. Locking Doors.
4. Adjustable shelves.
5. Loading capacity
MCU-201A, 301A, 401A, 340A, 580A:
110 lbs (50 kgs)
6. Grounded to prevent static electricity.

Specifications (Note: Specifications are subject to change due to product improvement.)

| ITEM | MODEL | MCU-201A | MCU-301A | MCU-401A | MCU-340A | MCU-580A |
|------------------------|-------|--|--|--|--|--|
| External Dimensions | | 19.7W x 21.0D x 24.8H (in) | 19.7W x 24.8D x 47.3H (in) | 19.7W x 24.8D x 61.0H (in) | 34.6W x 18.2D x 38.6H (in) | 34.6W x 30.0D x 38.6H (in) |
| Internal Dimensions | | 18.9W x 19.6D x 21.5H (in) | 18.9W x 23.6D x 43.2H (in) | 18.9W x 23.6D x 56.2H (in) | 33.9W x 16.7D x 33.1H (in) | 34.0W x 28.7D x 33.0H (in) |
| Capacity | | Approx 4.8 Cu Feet (135 Liters) | Approx 11 Cu Feet (310 Liters) | Approx 14 Cu Feet (400 Liters) | Approx 11 Cu Feet (300 Liters) | Approx 18.5 Cu Feet (520 Liters) |
| Dry Unit | | USF-3200 | USF-4000 | USF-4000 | USF-4000 | US-5000F |
| Material | | High-grade steel construction with ESD-safe and Anti corrosion coating | High-grade steel construction with ESD-safe and Anti corrosion coating | High-grade steel construction with ESD-safe and Anti corrosion coating | High-grade steel construction with ESD-safe and Anti corrosion coating | High-grade steel construction with ESD-safe and Anti corrosion coating |
| Color | | Ivory | Ivory | Ivory | Ivory | Silver |
| Doors (Magnetic) | | 1 Door with glass window | 2 Doors with glass windows | 3 Doors with glass windows | 2 Doors with glass windows | 2 Doors with glass windows |
| Weight | | Approx 66 lbs. (30 kgs.) | Approx 132 lbs. (60 kgs) | Approx 154 lbs. (70 kgs.) | Approx 128 lbs. (58 kgs.) | Approx 176 lbs. (80 kgs.) |
| Electrical Requirement | | AC 120V (50/60Hz) 20W/h Max 155W | AC 120V (50/60Hz) 25W/h Max 240W | AC 120V (50/60Hz) 25W/h Max 240W | AC 120V (50/60Hz) 25W/h Max 240W | AC 120V (50/60Hz) 28W/h Max 350W |
| Accessories Included | | 4 shelves, Locks, RH meter, Ground terminal | 8 shelves, Locks, RH meter, Ground terminal | 8 shelves, Locks, RH meter, Ground terminal | 3 shelves, Locks, RH meter, Ground terminal | 3 shelves, Locks, RH meter, Ground terminal |